



TECHNICAL DATA SHEET

SHIELDSEAL PRIMER

DESCRIPTION: SHIELDSEAL PRIMER is a Ultra Premium, high adhesion, quick drying water based acrylic Sealer/Primer.

RECOMMENDED USE: Formulated to penetrate, prime and seal. Its fine particle size gives it enhanced adhesion on Metal roofs including COLORBOND® and plain Zincalume in preparation for the THERMOBOND or ROOFBOND PREMIUM coating systems..

APPLICATION PROCESS: Refer to topcoat data sheet. Shieldcoat recommended surface preparation is crucial and is the responsibility of the Builder/Contractor/Applicator. Weather conditions must be considered and deemed suitable before proceeding. High humidity will affect drying and recoat times.

APPLICATION DETAILS / GUIDE:

Application method: Airless spray / Brush / Roller

Thinner: Not recommended (use Shieldcoat Hot Weather Additive sparingly)

Airless Tip Size: 515-LP517

Clean up: Water

Indicated film thickness: 120 microns (WFT)

Indicated film thickness: 55 microns (DFT)

Coats Required: 1 (Mist Coat Only)

TYPICAL PROPERTIES:

Colour: Grey (Some custom colours available)

Finish: n/a

Size: 15 Ltr

Volume solids: 25% average**



TECHNICAL DATA SHEET

SHIELDSEAL PRIMER

Theoretical spreading rate: 2-3m²/ltr

Application surface temperature: 10°C to 40°C

Touch Dry: 30 minutes*

Recoat: 2 hours *

Full Cure: 10-14 days*

Drinking Water Safe: After 10 days* curing and initial rinse (rain or garden hose pressure).

Shelf life: 24 Month

*All figures are quoted at 25° Celsius and 50% Relative Humidity

Solid content, weight % : 62 ± 1

Minimum Viscosity at 30°C

Brookfield RVT, 2 /20, Ps : 2 – 10

pH (1:1 with water) : 5.5 – 7



TECHNICAL DATA SHEET

SHIELDSEAL PRIMER

HEALTH AND SAFETY:

Contact The Poisons Information Center on Phone: 0800 764 766 or a doctor.

Ingestion: Do not induce vomiting. Give water to drink. Seek medical assistance.

Eye Contact: Flush eyes using eye baths until irritation subsides. Seek medical assistance.

Inhalation: Remove to fresh air. Seek medical assistance

Skin Contact: Wash thoroughly with soap and water. Launder clothing before reuse. Seek medical assistance if irritations persist.

Medical attention: Treat symptomatically.

First Aid Facilities: Eye Baths, safety showers.

RECOMMENDATIONS AND PRECAUTIONS:

Ensure that appropriate workplace health and safety methods and PPE are used when working with this product.

Ventilation: Ensure adequate ventilation when using this product.

Drinking water: When drinking water collection systems are in place, Shieldcoat recommends disconnecting the system prior to commencing work, then allowing 10 days of curing and a thorough fresh water rinse (rain or garden hose pressure) before reconnecting the system. Ensure that this product is applied in full accordance with Shieldcoat Recommendations.

Care and Maintenance: Protect the coating from abrasive contact for 10 days. Wash down periodically with a mild detergent solution to refresh and preserve the coating.

MSDS: Available on request or download from the Shieldcoat website. www.shieldcoat.co.nz

DISCLAIMER: Shieldcoat advises that the applicator of this product is responsible to determine and verify its suitability for the intended use prior to application. The data and recommendations contained within this document were true and accurate at the time of writing.